



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-18GHz..... 1.10:1 (Max)
 18-27GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

DIRECTION OF VIEW

UNIT
mm

TITLE
SMA Connector

DRAWN Shaohqing Du
CHECKED Haijin Zhang
APPR. Gang Cao

DWG NO.
D550S09F01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE A4-h | **SCALE**: 1 | **REV.** V2.0 | **SHEET** 1/1

1 2

5 6