



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-8GHz
 VSWR: DC-8GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING
 IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT
 PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
BNC Adapter

DWG NO.
Z525200Z01

| DATE | APPR. |
|------|-------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

DRAWN Min Zhou
 CHECKED Shaoqing Du
 APPR. Gang Cao

FINISH DIMENSIONS SPECIFIED
 1. HOLE: ALL DIMS BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SHARP FINISH

DO NOT SCALE DRAWING

SIZE A4_h SCALE: 1 REV. V2.0 SHEET 1/1