



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganaguan Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT  
 mm

TITLE  
**N Adapter**

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR: Gang Cao

DWG NO.  
**Z343400Z01**

LTR	DESCRIPTION	DATE	APPR.

1. REMOVE ALL DIMENSIONS FROM ALL CORNERS, SHARP EDGES, & ON H. MAX  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHING

DO NOT SCALE DRAWING

**OUTLINE DRAWING**