



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganabua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

**DIRECTION OF VIEW**  
  
 DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR: Gang Cao

**UNIT**  
 mm

**TITLE**  
 N Adapter

**DWG NO.**  
 Z343411Z01

**OUTLINE DRAWING**

LTR	DESCRIPTION	DATE	APPR.

**DO NOT SCALE DRAWING**

SIZE: A4\_h SCALE: 1 REV: V2.0 SHEET 1/1