



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganeshua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DRAWN	Shao Qing Du
CHECKED	Min Hai Zhang
APPR.	Gang Cao

DIRECTION OF VIEW	UNIT
	mm

TITLE	DWG NO.
N-N Adapter	Z343410F01

LTR	DESCRIPTION	DATE	APPR.

SIZE	A4_h	SCALE	4:1	REV.	V2.0	SHEET	1/1
------	------	-------	-----	------	------	-------	-----

**OUTLINE DRAWING**