

Performance Features:


Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALLWINTERK.COM

DIRECTION OF VIEW		UNIT	TITLE	
		mm	N Adapter	
DRAWN	Weihao Pan		DWG NO.	
CHECKED	Haimin Zhang		Z343410W01	
APPR.	Gang Cao		OUTLINE DRAWING	
<small>UNLESS OTHERWISE SPECIFIED 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1, ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</small>			DO NOT SCALE DRAWING	
LTR	DESCRIPTION	DATE	APPR.	SIZE A4_h
				SCALE 2: 1
				REV. V2.0
				SHEET 1/1