



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-27GHz  
 VSWR: DC-27GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI&PTFE



4th Floor, West Unit,  
 Incubation Building 1  
 Ganqianba Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT  
mm

TITLE  
SMA Adapter

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR. Gang Cao

DWG NO.  
Z555510Z01

LTR	DESCRIPTION	DATE	APPR.

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 3. DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

DO NOT SCALE DRAWING

SIZE: A4\_h SCALE: 4:1 REV: V2.0 SHEET: 1/1

1 2

5 6