



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI&PTFE



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Ln, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALMVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaoqing Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.
 DO NOT SCALE DRAWING

TITLE
SMA Adapter

DWG NO.
Z555511Z01

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.

SIZE	A4_h	SCALE:	1	REV.	V1.1	SHEET	1/1
------	------	--------	---	------	------	-------	-----