



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqianba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	Shaoping Du	UNIT	mm
CHECKED	Haimin Zhang		
APPR.	Gang Cao		

UNLESS OTHERWISE SPECIFIED:
 1. HOLE, ALL DIMS, UNLESS ALL DIMS, SHOW DIMS, 0.05 IN MIN.
 2. DIMENSIONS ON CROWN CORNERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISH: Ra

LTR	DESCRIPTION	DATE	APPR.

TITLE
SMA-SMA Adapter

DWG NO.
Z555500Y03A

OUTLINE DRAWING

SIZE	A4_h	SCALE	1:1	REV.	V2.0	SHEET	1/1
------	------	-------	-----	------	------	-------	-----