



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE



4th Floor, West Unit,
 Invention Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
SMA Adapter

DRAWN Min Zhou
 CHECKED Shaoqing Du
 APPR. Gaoq Cao

DWG NO.
Z555500W01

LTR	DESCRIPTION	DATE	APPR.

FINISH DIMENSIONS SPECIFIED
 1. REMOVE ALL DIMS, BREAK ALL CORNERS, SHARP EDGES (0.05 R MAX)
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES

DO NOT SCALE DRAWING

OUTLINE DRAWING

1 2

5 6

SHEET 1/1