



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-27GHz  
 VSWR: DC-27GHz.... 1.25:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PTFE



4th Floor, West Unit,  
 Invention Building 1  
 Guanghua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

**DIRECTION OF VIEW**

**UNIT**  
mm

**TITLE**  
SMA Adapter

**DRAWN** Min Zhou  
**CHECKED** Shaoping Du  
**APPR.** Gang Cao

**DWG NO.**  
Z555510W01

LTR	DESCRIPTION	DATE	APPR.

**DO NOT SCALE DRAWING**

**SIZE** A4\_h | **SCALE**: 1 | **REV.** V2.0 | **SHEET** 1/1

**OUTLINE DRAWING**