



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE



4th Floor, West Unit,
 Invention Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN Min Zhou
 CHECKED Shaoqing Du
 APPR. Gaoq Cao

UNLESS OTHERWISE SPECIFIED:
 1. HONEY ALL DIMENSIONS
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES

TITLE
SMA Adapter

DWG NO.
Z555511W01

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.

SIZE	A4_h	SCALE:	1	REV.	V2.0	SHEET	1/1
------	------	--------	---	------	------	-------	-----