



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-33GHz
 VSWR: DC-33GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabua Ln, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

UNIT
 mm

TITLE
3.5mm Adapter

DWG NO.
Z353510Z01

LTR	DESCRIPTION	DATE	APPR.

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. HOLE SIZE SHALL BE H7/g6 UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHING

DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1

OUTLINE DRAWING

1 2

5 6