



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-33GHz
 VSWR: DC-33GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIN TECHNOLOGY.



UNIT
 mm

TITLE
 3.5mm Adapter

DRAWN	Xiaolu Yu
CHECKED	Shaoling Du
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. HONED ALL DIMENSIONS.
 2. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SERVICE FINISHES

DO NOT SCALE DRAWING

DWG. NO.
 Z353500Y02

OUTLINE DRAWING

1 2

5 6

SHEET 1/1