



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqianba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT
 mm

TITLE
2.92mm Adapter

DRAWN: Shaogqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

DWG NO.
Z363610Z01

1. REMOVE ALL DIMENSIONS SPECIFIED.
 2. HONOR ALL DIMENSIONS.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS FINISHES ARE SPECIFIED.

DO NOT SCALE DRAWING

LTR	DESCRIPTION	DATE	APPR.

SIZE	SCALE	REV.	SHEET
A4_h	1	V2.0	1/1

1 2

5 6