



Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz... 1.20:1 (Max)  
**Materials/Finishes:**  
 Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Inchedation Building 1  
 Guanghua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW

UNIT  
 mm

TITLE  
**2.92mm Adapter**

DRAWN Weihao Pan  
 CHECKED Haijin Zhang  
 APPR. Gang Cao

DWG NO.  
**Z363610FS09**

LT#	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING  
 SIZE A4\_h SCALE: 1 REV. V2.0 SHEET 1/1

1 2

5 6