



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.20:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganaguan Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm

DRAWN	Shaoping Du
CHECKED	Haimin Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 1. HOLE, ALL DIMENSIONS ARE IN MILLIMETERS.
 2. DIMENSIONS ON CIRCULAR FEATURES TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON ANGULAR FEATURES TO BE TO THE VERTEX UNLESS OTHERWISE SPECIFIED.
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES:

LTR	DESCRIPTION	DATE	APPR.

TITLE	2.92mm Adapter
DWG NO.	Z363600YS02

OUTLINE DRAWING

SIZE	A4_h	SCALE	4:1	REV.	V2.0	SHEET	1/1
------	------	-------	-----	------	------	-------	-----