



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz... 1.25:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Innovation Building 1  
 Guanghua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

**DIRECTION OF VIEW**

MIN ZHOU

**UNIT**

mm

**TITLE**

2.92mm Adapter

**DRAWN** Min Zhou

**CHECKED** Shaoping Du

**APPR.** Gang Cao

**DWG NO.**

Z363610W01

1. REMOVE ALL DIMENSIONS SPECIFIED.  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

**DO NOT SCALE DRAWING**

**OUTLINE DRAWING**

LTR	DESCRIPTION	DATE	APPR.

<b>SIZE</b> A4_h	<b>SCALE</b> 1:1	<b>REV.</b> V2.0	<b>SHEET</b> 1/1
------------------	------------------	------------------	------------------