



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz... 1.20:1 (max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganeshan Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Shaohqing Du
CHECKED	Haimin Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 1. MATERIAL: ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CIRCULAR FEATURES TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON ANGULAR FEATURES TO BE MEASURED TO THE VERTEX UNLESS OTHERWISE SPECIFIED.
 4. ALL DIMENSIONS ARE AFTER FINISHING. SOURCE FINISHING.

LTR	DESCRIPTION	DATE	APPR.

TITLE
2.4mm Adapter

DWG NO.
Z373700FS01

OUTLINE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET 1/1