



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-50GHz  
 VSWR: DC-50GHz... 1.20:1 (Max)

**Materials/Finishes:**

Housings: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Guanchuan Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

**DIRECTION OF VIEW**  
  
 DRAWN: Shaoqing Du  
 CHECKED: Haijin Zhang  
 APPR.: Gaiqiang Cao

**UNIT**  
 mm

**TITLE**  
 2.4mm Adapter  
 DWG NO. Z373700YS02C

**OUTLINE DRAWING**

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING	SIZE: A4-h	SCALE: 4:1	REV. V2.0	SHEET 1/1
----------------------	------------	------------	-----------	-----------