



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz..... 1.10:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqian Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT
 mm

DRAWN: Shaohqing Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

1. MAKE ALL DIMENSIONS SPECIFIC.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE NOTED.

LTR DESCRIPTION DATE APPR. DO NOT SCALE DRAWING

TITLE
 APC7mm-3.5mm Adapter

DWG NO.
 Z3335N0Z01

OUTLINE DRAWING

SIZE: A4_h SCALE: 1 REV: V1.1 SHEET: 1/1