



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.10:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganqunba Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.



UNIT  
mm

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR.: Gang Cao

1. MAKE ALL DIMENSIONS CLEAR UNLESS SHOWN OTHERWISE.  
 2. DIMENSIONS ON CROWN CENERS TO BE CONSIDERED UNLESS NOTED.  
 3. DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

LTR	DESCRIPTION	DATE	APPR.

TITLE  
APC7mm-3.5mm Adapter

DWG NO.  
Z3335N1Z01

OUTLINE DRAWING

SIZE: A4\_h SCALE: 1 REV. V1.1 SHEET 1/1