



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
           Polished & Passivated  
 Center Contact: Beryllium Copper  
                   Gold Plated  
 Insulators: PEI

 <p>4th Floor, West Unit, Incubation Building 1 Guanghua Lu, Nanjing TEL: 025-84304950 FAX: 025-84304959 WWW.ALLWINTEK.COM</p>	DIRECTION OF VIEW		UNIT	TITLE
			mm	L16-N Adapter
	DRAWN	Min Zhou	DWG NO.	
	CHECKED	Shaoqing Du	Z313410Z01	
APPR.	Gang Cao	OUTLINE DRAWING		
<small>PROPRIETARY INFORMATION. THE INFORMATION WHEN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLWIN TECHNOLOGY.</small>		<small>UNLESS OTHERWISE SPECIFIED:          1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX          2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1°          3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1          4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</small>		SIZE A4_h    SCALE 4:1    REV. V2.0    SHEET 1/1
LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING