



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganephua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

1. EXCESS DIMENSIONS SPECIFIED.
 2. HONED ALL HORIZONTAL SURFACES.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING. SOURCE FINISHING.

LTR	DESCRIPTION	DATE	APPR.

TITLE
N-2.92mm Adapter
 DWG NO.
Z343611Z01

OUTLINE DRAWING

SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1