



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz ... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganqianba Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



DIRECTION OF VIEW  
 UNIT  
 mm

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR.: Gang Cao

DWG NO.  
 Z343700Z01

TITLE  
 N-2.4mm Adapter

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
|     |             |      |       |
|     |             |      |       |
|     |             |      |       |

1. UNLESS OTHERWISE SPECIFIED:  
 1. HORIZONTAL DIMENSIONS UNLESS OTHERWISE SPECIFIED  
 2. DIMENSIONS ON CIRCULAR PARTS TO BE CONCENTRIC WITHIN 0.1  
 3. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHES:  
 DO NOT SCALE DRAWING

SIZE: A4\_h SCALE: 1 REV: V2.0 SHEET: 1/1

1 2

5 6