



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz ... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqian Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

UNIT
 mm

TITLE
N-2.4mm Adapter

DWG NO.
Z343711Z01

LTR	DESCRIPTION	DATE	APPR.

1. DRAW ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.

DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET 1/1

OUTLINE DRAWING