



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-8GHz
 VSWR: DC-8GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI&PTFE
 Coupling Nut: Brass
 Nickel Plated



4th Floor, West Unit,
 Incehation Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW
 UNIT
 mm

DRAWN: Shaoqing Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

TITLE
N-BNC Adapter

DWG NO.
Z345211Z01

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.

SIZE	A4_h	SCALE:	1:1	REV.	V1.1	SHEET	1/1
------	------	--------	-----	------	------	-------	-----