



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-11GHz
 VSWR: DC-11GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
N-TNC Adapter

DWG NO.
Z345310Z01

LTR	DESCRIPTION	DATE	APPR.

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 1. HOLE, ALL DIMS, UNLESS ALL DIMS, SHOWN, SHALL BE IN MM
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES
 DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V1.1 SHEET: 1/1

OUTLINE DRAWING