



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-11GHz
 VSWR: DC-11GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALUMINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
N-TNC Adapter

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

DWG NO.
Z345311Z01

1. REMOVE ALL DIMENSIONS AND DIMENSIONS SHOWN UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CIRCULAR PARTS TO BE CONCENTRIC UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON CIRCULAR PARTS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHES:
 DO NOT SCALE DRAWING

OUTLINE DRAWING

SIZE: A4_h SCALE: 1:1 REV: V1.1 SHEET: 1/1

LTR	DESCRIPTION	DATE	APPR.

1 2

5 6