



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz... 1.25:1(Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI

		4th Floor, West Unit, Incubation Building 1 Guanghua Lu, Nanjing TEL: 025-84304950 FAX: 025-84304959 WWW.ALLWINTEK.COM		DIRECTION OF VIEW 		UNIT mm		TITLE N-TNCA Adapter	
PROPRIETARY INFORMATION: THE INFORMATION WITHIN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLWIN TECHNOLOGY.				DRAWN: Shaoqing Du CHECKED: Haimin Zhang APPR.: Gang Cao		DWG NO. Z345411Z01			
UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓				DO NOT SCALE DRAWING		SIZE A4_h		SCALE 4:1	
LTR		DESCRIPTION		DATE		APPR.		REV. V2.0	
								SHEET 1/1	