



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganachua Ln, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW  

 UNIT  
 mm

DRAWN: Xiaoli Yu  
 CHECKED: Shaoping Du  
 APPR: Gang Cao

TITLE  
**N-SMA Adapter**

DWG NO.  
**Z345501FS10A**

LTR	DESCRIPTION	DATE	APPR.

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHES:  
 DO NOT SCALE DRAWING