



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-33GHz  
 VSWR: DC-33GHz... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganeshua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT  
 mm

TITLE  
 2.92mm - 3.5mm Adapter

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR: Gang Cao

DWG NO.  
 Z353601Z01

1. UNLESS OTHERWISE SPECIFIED:  
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1  
 3. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES

DO NOT SCALE DRAWING

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
|     |             |      |       |
|     |             |      |       |

| SIZE | SCALE | REV. | SHEET |
|------|-------|------|-------|
| A4_h | 1:1   | V1.1 | 1/1   |

1 2

5 6