



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-33GHz  
 VSWR: DC-33GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganababu Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DIRECTION OF VIEW  
  
 UNIT  
 mm

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR. Gang Cao

UNLESS OTHERWISE SPECIFIED:  
 1. RADII, ALL DIMENSIONS, ALL CORNERS, SHARP EDGES, UNLESS OTHERWISE SPECIFIED, TO BE CONFORMANT WITH ISO 1191.  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1.  
 3. DIMENSIONS ARE AFTER PLATING, SURFACE FINISH SW7.  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISH SW7.

LTR	DESCRIPTION	DATE	APPR.

TITLE  
**2.4mm-3.5mm Adapter**

DWG NO.  
**Z353700Z01**

**OUTLINE DRAWING**