



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz... 1.20:1 (Max)  
 Power Handling: 0.5W

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganqian Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

UNIT  
 mm

TITLE  
 2.92mm Load

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR.: Gang Cao

DWG NO.  
 T361P0Z01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE: A4\_h SCALE: 1 REV: V2.0 SHEET 1/1