



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz... 1.25:1 (Max)
 Power Handling: 0.5W

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganeshan Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	

DRAWN	Shaodong Du
CHECKED	Min Jhi Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED,
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER MATING. SOURCE FINISHES

DO NOT SCALE DRAWING

TITLE
2.4mm Load

DWG NO.
T371P0Z01

OUTLINE DRAWING

1	2	3	4	5	6
LTR	DESCRIPTION	DATE	APPR.	SIZE A4_h	SCALE: 1
					REV. V2.0
					SHEET 1/1