

Performance Features:

Nominal Impedance:50Ω
 Frequency Range:DC-50GHz
 VSWR:1.35:1(Max)
 Power Handling:0.5W

Materials/Finishes:


Housing:Stainless Steel,Passivated
 Center Contact:Beryllium Copper,Gold Plated
 Insulators:PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, Nanjing
 TEL:025-84304950
 FAX:025-84304959
 WWW.ALLWINTEK.COM

PROPRIETARY INFORMATION: THE INFORMATION WITHIN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLWIN TECHNOLOGY.

DIRECTION OF VIEW



UNIT

mm

TITLE

2.4-J Load

DRAWN

Ping Wang

CHECKED

Shaoqin Du

APPR.

Dong Wu

DWG NO.

T371P0Z01H

OUTLINE DRAWING

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX
 2. LINEARITY TOLERANCES ±0.2, ANGLE TOLERANCES ±1°
 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISH AS SHOWN

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE A4 a	SCALE 4:1	REV. V2.0	SHEET 1/1
------------------	------------------	------------------	------------------