



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz... 1.25:1 (Max)
 Power Handling: 0.5W

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaodong Du
 CHECKED: Min Hai Zhang
 APPR: Gang Cao

1. REMOVE ALL DIMENSIONS FROM ALL DIMENSIONS, SHOW DIMENSIONS TO CENTER UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ARE AFTER MATING, SINCE FINISHED.
 4. ALL DIMENSIONS ARE AFTER MATING, SINCE FINISHED.

LTR	DESCRIPTION	DATE	APPR.

TITLE
2.4mm Load

DWG NO.
T370P0Z01

OUTLINE DRAWING

SIZE	SCALE	REV.	SHEET
A4_h	1	V2.0	1/1