

Performance Features:

Nominal Impedance: 50Ω
Frequency Range: DC-27GHz
Operating Temperature: -60℃~+165℃

Materials/Finishes:

Housing: Brass
Gold Plated
Center Contact: Beryllium Copper
Gold Plated
Insulators: PTFE

ALLWIN TECHNOLOGY
4th Floor, West Unit, Incubation Building 1
Guanghua Lu, Nanjing
TEL: 025-84304950
FAX: 025-84304959
WWW.ALLWINTEK.COM

PROPRIETARY INFORMATION: THE INFORMATION WHIN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLWIN TECHNOLOGY.

LTR	DESCRIPTION	DATE	APPR.

DIRECTION OF VIEW

UNIT: mm

DRAWN	Shaoqing Du
CHECKED	Haimin Zhang
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIDE
1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX
2. LINEARITY TOLERANCES ±0.1, ANGLE TOLERANCES ±1°
3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISHED

DO NOT SCALE DRAWING

TITLE: SMA Connector

DWG NO.: D550B12E01-048

OUTLINE DRAWING

SIZE	SCALE	REV.	SHEET
A4_h	4:1	V2.0	1/1