



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganadhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaohqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

TITLE
2.92mm Connector

DWG NO.
D360S09F01

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
| | | | |
| | | | |
| | | | |

DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1

1 2

5 6