



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incheon Building 1
 Ganghwa I-d, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLWINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALWIN TECHNOLOGY.



DIRECTION OF VIEW
 UNIT
 mm

TITLE
2.92mm Connector

DRAWN: Xin Gong
 CHECKED: Haijin Zhang
 APPR: Gang Cao

DWG. NO.
D360S20F04

LTR	DESCRIPTION	DATE	APPR.

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL DIMENSION LINES AND DIMENSIONS SHOWN HEREIN.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.
 4. ALL DIMENSIONS ARE AFTER FINISHING SERVICE FINISHED.

DO NOT SCALE DRAWING

OUTLINE DRAWING