



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Ln, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLWINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALWIN TECHNOLOGY.



UNIT
 mm

TITLE
2.92mm Connector

DWG. NO.
D360S09F05

OUTLINE DRAWING

| DESCRIPTION | DATE | APPR. |
|-------------|------|-------|
| LTR | | |

| DRAWN | Yin Gong | DWG. NO. | SIZE | A4-h | SCALE | 4: 1 | REV. | V2.0 | SHEET | 1/1 |
|---------|--------------|----------|------|------|-------|------|------|------|-------|-----|
| CHECKED | Haijin Zhang | | | | | | | | | |
| APPR. | Gang Cao | | | | | | | | | |

1 2

5 6