



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incheon Building 1
 Ganghwa Iri, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLMINTK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.



UNIT
 mm

TITLE
2.92mm Connector

DRAWN: Xin Gong
 CHECKED: Haijin Zhang
 APPR: Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. HOLE ALL DIMENSIONS, UNLESS SPECIFIED, ARE IN MILLIMETERS.
 2. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC WITHIN 0.1
 3. ALL DIMENSIONS ARE AFTER FINISHING, SURFACE FINISH: Ra 0.4

DWG. NO.
D360S09F06

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

OUTLINE DRAWING