



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.



DIRECTION OF VIEW

UNIT
 mm

TITLE
 2.92mm Connector

DRAWN: Shaoqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. HOLE ALL DIMENSIONS, UNLESS SPECIFIED, ARE IN MILLIMETERS.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 4. ALL DIMENSIONS ARE AFTER FINISHING, SURFACE FINISHES AS SPECIFIED.

DWG. NO.
 D360S09F07

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE: A4-h SCALE: 4:1 REV. V2.0 SHEET 1/1

OUTLINE DRAWING

1 2

5 6