



**Performance Features:**

Nominal Impedance: 50 $\Omega$   
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz..... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Guanghua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW: ALLVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.



DIRECTION OF VIEW

UNIT  
mm

TITLE  
2.92mm Connector

DRAWN	Xin Gong
CHECKED	Haidin Zhang
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIED:  
 1. REMOVE ALL DIMENSIONS, ALL CORNERS, SHARP EDGES & OR R MAX  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER FINISHING SERVICE FINISHED

DO NOT SCALE DRAWING

DWG. NO.  
D360S20F07

OUTLINE DRAWING

SIZE A4-h SCALE: 4:1 REV. V2.0 SHEET 1/1

1 2

LTR DESCRIPTION DATE APPR.

1 2 3 4 5 6

1 2 3 4 5 6