

Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)


Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Ln, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLWINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIN TECHNOLOGY.



UNIT
 mm

TITLE
2.92mm Connector

DRAWN	Shaoqing Du
CHECKED	Haidin Zhang
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. HOLE ALL DIMENSIONS, UNLESS SPECIFIED, ARE IN MILLIMETERS.
 2. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC UNLESS NOTED OTHERWISE.
 3. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC UNLESS NOTED OTHERWISE.
 4. ALL DIMENSIONS ARE AFTER FINISHING, SURFACE FINISHES AS SPECIFIED.

DWG. NO.
D361S15F02

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE A4-h SCALE: 4:1 REV. V2.0 SHEET 1/1