



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incheubation Building 1
 Ganghwa Ln, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLMIVTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALMIV TECHNOLOGY.



UNIT
 mm

TITLE
2.92mm Connector

DWG. NO.
D361S09F05

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.

DRAWN	Shaoqing Du
CHECKED	Haidin Zhang
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL DIMENSIONS, ALL CORNERS, SHARP EDGES & OR R MAX
 2. DIMENSIONS ON DIMENSION LINES TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON DIMENSION CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER FINISHING SERVICE FINISHED ✓
 DO NOT SCALE DRAWING