



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Ln, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.



DIRECTION OF VIEW

UNIT
 mm

TITLE
 2.92mm Connector

DRAWN: Shaoqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

DO NOT SCALE DRAWING

DWG NO.
 D361S20F06

LTR	DESCRIPTION	DATE	APPR.

UNLESS OTHERWISE SPECIFIED:
 1. HOLE ALL DIMENSIONS, UNLESS SPECIFIED, ARE IN MILLIMETERS.
 2. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC UNLESS NOTED.
 3. DIMENSIONS ON COORDINATE SYSTEMS TO BE CONCENTRIC UNLESS NOTED.
 4. ALL DIMENSIONS ARE AFTER FINISHING, SURFACE FINISHES.

OUTLINE DRAWING

SIZE: A4-h SCALE: 4:1 REV: V2.0 SHEET: 1/1