



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz

**Materials/Finishes:**

Housing: SU303F  
 Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganahua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

**DIRECTION OF VIEW**



**UNIT**  
mm

**TITLE**  
2.92mm Connector

**DRAWN** Shaoping Du  
**CHECKED** Haimin Zhang  
**APPR.** Gang Cao

**DWG NO.**  
D360P0403F06

LTR	DESCRIPTION	DATE	APPR.

1. EXAMINE ALL DIMENSIONS, CHECK ALL CORNERS, SHARP EDGES, 0.05 & 0.04  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER MATING. SURFACE FINISHES  
**DO NOT SCALE DRAWING**

**OUTLINE DRAWING**

1 2

5 6

1 2 3 4 5 6

A

B

C

D

A

B

C

D