



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-50GHz  
 VSWR: DC-50GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganaguan Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT: mm

TITLE: 2.4mm Connector

DRAWN: Shiqiang Du  
 CHECKED: Haijin Zhang  
 APPR. Gaiqiang Cao

DWG NO. D370S20F05

LTR	DESCRIPTION	DATE	APPR.

1. UNLESS OTHERWISE SPECIFIED:  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER MATING. SURFACE FINISHES:  
 DO NOT SCALE DRAWING

SIZE: A4-h SCALE: 4:1 REV. V2.0 SHEET 1/1

OUTLINE DRAWING