



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT: mm

DRAWN: Shaohong Du
 CHECKED: Heimin Zhang
 APPR. Gaoqiang Cao

1. EXCESS DIMENSIONS SPECIFIED.
 2. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER FINISHING. DO NOT SCALE DRAWING.

TITLE
2.4mm Connector

DWG NO.
D371S12F04

OUTLINE DRAWING

SIZE: A4-h SCALE: 4:1 REV. V2.0 SHEET 1/1